



Stock #CB33

One (1) GE Drawout Circuit breaker Type VB1-4.16-250-3

1200 amps, 4.76 kv, 60 kv BIL, rated short circuit amps 29 KA, 5 cycle,  
Serial number 0366A5503-001-01, control voltage 48 vdc trip and close  
, Mech type ML-18, built 2/99 no. of Ope 2828, vac type 52B1

Shipping size: 40" x40" x 43" 520 lbs



**GE Power Vac Breaker** TYPE VB1 4.16-250-3  
SER. NO. 0366A5503-001-01

RATED MAX VOLTAGE	4.76 KV	RATED AMP.	1200	HZ	60	IMPULSE WITHSTAND	60	KV <sup>INT</sup> TIME	5	CYC
RATED SHORT CIRCUIT AMPS	29 KA	RATED VOLTAGE RANGE FACTOR	1.24			CLOSE & LATCH CAPABILITY AMP.	58	KA		
CLOSE COIL	0209B8103G008	VOLTS	48VDC			CLOSING AMPS	13.7	VOLT RANGE	30-120	
TRIP COIL-1	0209B8104G001	VOLTS	48VDC			TRIPPING AMPS.	17	VOLT RANGE	240-250	
TRIP COIL-2		VOLTS				TRIPPING AMPS.		VOLT RANGE		
CHARGING MOTOR	0177C5050G006	VOLTS	48VDC		HZ					
CONNECTION DIAGRAM	0209B8250P001	WT	470LBS			MECH TYPE	ML-18	DATE MFG.	2/99	
VAC. INTER. TYPE	52B1	REQ.:	M19-22139			SO:	924000			

**CAUTION:** BEFORE INSTALLING OR OPERATING READ INST. GEK-83132

GE  
ELECTRICAL DISTRIBUTION & CONTROL  
BURLINGTON, IOWA 52601 USA

0282A2001P002