

NSV Energy LLC
35 Hickory Springs Industrial Drive
Canton GA 30115



Stock # VFD17

Two (2) Allen Bradley PowerFlex 4 VFD, Cat# 22A-D4P0N104 Series A . 2 hp, input 380 -480 V AC 50/60 hz, 5.7 amps ,output 0- 240 hz. 0-460 v, 4 amps Manufactured 2017, C(UL) listed, Made in China Shipping size 9" L x 9" W x 9" H 3 lbs



Cat No. 22A-D4P0N104 SERIES A

IP20 / UL Open-Type with top cover removed (rated -10°C to 50°C Ambient)
IP30 / NEMA 1 / UL Type 1 with top cover and optional conduit box kit installed (rated -10°C to 40°C Ambient). Refer to user manual.

Motor Rating: 1.5kW/2.0HP

Input: 3 Phase, 380- 480V, 48-63Hz
AC Voltage Range: 342-528
Amps: 5.7

Output: 3 Phase, 0-240Hz
AC Voltage Range: 0- 460
Continuous Amps: 4.0
60 Sec Ovd Amps: 6.0

SHORT CIRCUIT CURRENT : 100kA
POWER TERMINAL WIRE:
Use 75°C Cu Wire
3 3mm² -0.8 mm² (12-18 AWG)
Torque 1.96 Nm (17.4 in.-lbs.)

Rockwell Automation
1201 S 2nd St, Milwaukee, WI 53204, USA
生产日期 MFD - IN 2017 ON NOV - 21
S/N: AD4P0N0W17470208
FRN: 7.01

UL US LISTED IND. CONT. EQ. E59272

CE
EAC

AB Allen-Bradley PRODUCT OF CHINA