



Stock # T89

Siemens dry type Transformer 225 kva, 3 phase, 60 hz , Catalog No 3G5Y225, Model 36B, impedance 5.83 % winding rise 150 deg C insul. Class 220 deg C, Type 2 enclosure , serial no. 201922, UL listed, Made in USA

Primary voltage: 600 Delta 10 kv BIL Taps 633-614-600-581-567-554-541

Secondary voltage 480Y/277, 10 kv BIL

Shipping Dimension: 48" L x 35"W x 56" H 1330 LBS



SIEMENS

Siemens Energy & Automation, Inc.
 DRY TYPE TRANSFORMER

CATALOG NO. 3G5Y225
 OPTIONAL WEATHERSHIELDS CAT.#DSK-20

225 KVA @150C RISE IMP 5.83 %

PRIMARY 600 (H)

SECONDARY 480Y/277 (X)

WEIGHT 1320 LBS. 60HZ 3 PHASE

220 C INSULATION SYSTEM FH4G

AMBIENT TEMP 40 C MAX

SERIAL NO. 201922
 FILE E37783

COIL TAP ARRANGEMENT

$\frac{4}{3} \frac{4}{5} \frac{2}{7}$	$\frac{4}{3} \frac{4}{5} \frac{2}{7}$	$\frac{4}{3} \frac{4}{5} \frac{2}{7}$
---------------------------------------	---------------------------------------	---------------------------------------

TAP	VOLTS	AMPS
2 TO 3	633	205
2 TO 5	614	212
3 TO 4	600	216
4 TO 5	581	224
5 TO 6	567	229
4 TO 7	554	234
6 TO 7	541	240

LISTED
POWER
TRANSFORMER 641H

MODEL 36 B

TYPE 2 ENCLOSURE, TYPE 3R ENCLOSURE WHEN PROVIDED
 WITH WEATHERSHIELDS PART NO. 225TR3
 BEFORE HANDLING, INSTALLING AND OPERATING, SEE INSTRUCTION IN-7700
 ALUMINUM CONDUCTOR PRIMARY: 10 KV BIL SECONDARY: 10 KV BIL
 SIX INCH MINIMUM CLEARANCE IS REQUIRED FROM WALLS OR OTHER OBSTRUCTIONS FOR ALL VENTILATION OPENINGS

DRY TYPE TRANSFORMER CLASS AA **MADE IN U.S.A.**

www.nsvenergy.com

sales@nsvenergy.com

908-421-4139