

Stock # T54

One (1) Hammond three phase dry transformer 75 kva, 3 phase, 60 hz, 150 Deg C rise 5.9 % Imp, Part no MK075KB , Cooling ANN, 220 deg C insulation system Encl NEMA-3R, AL winding

Primary voltage: 480 v delta taps: 504-492-480-468-456-444-432

Secondary voltage 208Y/120 V UL listed , with Siemens heavy duty switch on Two sides. 600 v, 100 amps with one side 70 amps fuses and other side 80 amps fuses.

Shipping size 54" x 38" x 45" H ' H 620 lbs



**HPS** Hammond Power Solutions Inc.  
 GUELPH, ONT. BARABOO, WI COMPTON, CA MONTERREY, MX

UL LISTED DRY TYPE TRANSFORMER 7705 112313

**THREE PHASE DRY TYPE TRANSFORMER**  
**TRANSFORMATEUR SEC TRIPHASÉ**


HV/HT **480V** Cust. Ref.   
 BIL  Serial No.   
 TERM. BORNES **H1 H2 H3** Part No. **MK075KB**  
 No. de pièce **75**

VOLTS	CURRENT COURANT	% RATED VOLTAGE % TENSION NOMINALE	CONNECTIONS EACH PHASE CONNEXION PAR PHASE
504	85.9	105	1
492	88.0	102.5	2
480	90.2	100	3
468	92.5	97.5	4
456	95.0	95	5
444	97.5	92.5	6
432	100.2	90	7

LV/VT **208Y/120V**  
 BIL   
 TERM. BORNES **X0 X1 X2 X3**

TYPE **K**  
 Cooling **ANN**  
 Temp. Rise **150 C**  
 Échauffement **150 C**  
 Temp. Class **220 C**  
 Classe de Temp.  
 Frequency **60 Hz**  
 Impédance % **5.9**  
 Encl. Type **NEMA-3R**  
 Type de boîtier  
 Wt. LBS **520**  
 Poids en lbs.  
 Winding **AL**  
 Enroulement

SPACINGS BETWEEN ENCLOSURE AND AIR ADJACENT WALL SHALL BE A MINIMUM OF 6 INCHES



8 03423 01390 5

