

NSV Energy LLC
 35 Hickory Springs Industrial Drive
 Canton GA 30115



Stock # T94

ReX Isolation Transformer 145 kva, 3 phase, 60 hz , Cat No. DA145H1P1/K4, Type ANN, imp. 4 % winding rise 150 deg C insul. Class 220 deg C., Enclosure type-2 , Serial no. C 05, UL listed, winding CU/AL, BIL 10 KV , Made in Canada

Primary voltage: 460 Delta Taps 483--472-460-449-437 or 480 V delta

Secondary voltage 460 Y/266 v or 480 Y/277

Shipping Dimension: 40" L x 36" W x 37" H 958 lbs



SUITABLE FOR NONSINUSOIDAL CURRENT LOAD WITH A K FACTOR NOT EXCEED 4
 N.C. THERMOSTAT RATED @200 DEGREE C.
 240 VOLT AT 1.5 AMPS
 120 VOLT AT 3.0 AMPS

UL LISTED POWER TRANSFORMER 800V

REX MANUFACTURING
 DIVISION OF TRANSFACTOR INDUSTRIES INC.
 REXDALE, ONT.

CAT. NO. DA145H1P1/K4	KVA 145	ENCL. TYPE-2
SERIAL C 05	HZ 60	TYPE ANN
TRANSFORMER 3 PH ISO.	% IMP. 4.0	AT 170 C.
INSULATION CLASS 220 C.	TEMPERATURE RISE 150 C.	
PRI. VOLTAGE 460 DELTA	H1-H2-H3	BIL. 10 KV.
SEC. VOLTAGE 460Y/266	X0-X1-X2-X3	WT. 980 LBS.

PRI. VOLTAGE	CONNECTION CONNECTION
105.00%	1-1-1
102.5%	2-2-2
100.0%	3-3-3
97.5%	4-4-4
95.0%	5-5-5

CU-AL

REX MANUFACTURING
ISOLATION TRANSFORMER

WEATHER RESISTANT NEMA 3R RATED WHEN OPTIONAL WEATHER SHIELD KIT # H IS INSTALLED