

NSV Energy LLC
 35 Hickory Springs Industrial Drive
 Canton GA 30115



Stock # T99

MGM dry type Transformer 112.5 kva, 3 phase, 60 hz , Type HT, with Electrostatic shield, Catalog No . HT112A3K2SH, impedance 6.16 % winding rise 150 deg C, insul. Class 220 deg C., Enclosure type 1, UL listed, Made in USA

Primary voltage: 480 Delta Taps 504-492-480-468-456-444-432, Secondary voltage 240/120

Shipping Dimension: 48" x 48" x 46" 716 lbs



MGM TRANSFORMER COMPANY
 CITY OF COMMERCE, CA 90040
 (800) 423 4366 WWW.MGMTRANSFORMER.COM

DRY TYPE TRANSFORMER

112.5 KVA THREE PHASE 60 HERTZ TYPE HT
 VOLTAGE 480 - 240/120 C.T. W/(1) ELECTROSTATIC SHIELD
 INSUL. SYS. 220° C 150° C RISE COOLING CLASS "AA"
 CAT. NO. HT112A3K2SH IMPEDANCE 6.16% AT 170° C
 S/N 112DSN-0612-5-18 WEIGHT 730 LBS APPROX.

CONNECT TAPS	VOLTAGE
4 - 5	504
4 - 6	492
3 - 5	480
3 - 6	468
2 - 6	456
3 - 7	444
2 - 7	432

MINIMUM CLEARANCE FROM TRANSFORMER ENCLOSURE TO WALL OR OTHER OBSTACLE IS 6 INCHES.
 ABOVE CLEARANCE IS FOR VENTILATION PURPOSE ONLY AND IS NOT INTENDED TO REPLACE OR
 TAKE PRECEDENT OVER NATIONAL, STATE AND LOCAL CODES WHICH MAY REQUIRE LARGER
 CLEARANCES.

UL LISTED **DRY TYPE POWER TRANSFORMER** **NSI**

DANGER - HAZARD OF ELECTRICAL SHOCK OR FIRE - TURN OFF POWER