





Stock # SEL19

SEL-751A Feeder protection relay, Part # **751A51A0X0X71850001**, Power supply 125/250 vdc ,  
 120/240 Vac 50/60 hz, S/N 3163540348, Made in USA

Shipping size: 12" x 12" x 12" 8.3 lbs



|  |  |  |
|--|--|--|
| P/N 751A51A0X0X71850001<br>S/N 3163540348  |  | <br>CLASS 2258 02<br>CLASS 2258 82<br>Process Control Equipment<br>for Hazardous Locations -<br>Certified to Canadian and<br>US Standards.  |
| Supply Range (U <sub>s</sub> ) 125 / 250V ---<br>120 / 240V ~ 50 / 60Hz<br>VA Rating 40 VA / 20W<br>Internal Fuse T3.15A H 250V<br>Rated Impulse Withstand (U <sub>imp</sub> ) 4kV<br>Insulation Voltage (U <sub>i</sub> ) 300V  | <br>CE<br>Applicable hazardous locations (North America),<br>Class I, Division 2, Groups A, B, C, D, T4.<br>Endroits dangereux applicables (Amérique du Nord),<br>Classe I, Division 2, Groupes A, B, C, D, T4. |  |
| <b>CONTACT OUTPUTS (OUT101-OUT103)</b><br>Operational Voltage (U <sub>e</sub> ) 240V ~ MAX<br>Operational Current (I <sub>e</sub> ) 3A @ 120V<br>1.5A @ 240V<br>Thermal Current (I <sub>the</sub> ) 5A<br>Utilization Category AC-15<br>Contact Rating Designation B300<br>Insulation Voltage (U <sub>i</sub> ) 300V<br>Short-Circuit Rating 1kA |  | <br>For use in Pollution Degree 2 environment.<br>See instruction manual for details.<br>WARNING - EXPLOSION HAZARD -<br>Open circuit before removing cover.<br>WARNING - EXPLOSION HAZARD - Substitution<br>of components may impair suitability for Class I, Division 2.<br>Operating temperature range: -40°C to +85°C<br>Hazardous Locations operating temperature<br>range: -20°C to +40°C<br>Ambient air temperature shall not exceed 50°C<br>Pour l'utilisation dans un environnement de Degré de Pollution 2.<br>Voir le manuel d'instructions pour plus de détails.<br>AVERTISSEMENT - DANGER D'EXPLOSION -<br>Ouvrir le circuit avant de déposer le couvercle.<br>AVERTISSEMENT - DANGER D'EXPLOSION - La substitution<br>de composants peut détériorer la conformité à<br>Classe I, Division 2.<br>Plage de température de fonctionnement: -40°C à +85°C<br>Emplacements dangereux: -20°C à +40°C<br>La température de l'air ambiant ne doit pas dépasser 50°C |
| <b>OPTIONAL OUTPUTS / INPUTS</b><br>See instruction manual for details.<br>Voir le manuel d'instructions pour plus de détails.   |  | This product may be covered by one or more<br>of the following U.S. Patents:<br>5,515,227 6,910,804 8,593,769<br>5,793,750 7,480,580 8,664,961<br>6,639,413 7,720,619 8,679,329<br>6,855,835 8,140,283 8,735,799<br>6,743,291 8,219,173 8,493,773<br>6,757,146 8,346,402 8,618,616<br>6,489,295 8,491,572 8,619,480<br>USA<br>Other U.S. Patents Pending. Foreign Patents issued and pending 459-0454 J  |
| <br>2350 NE Hopkins Curve<br>P.O. Box 10000<br>Hillsdale, WA, USA 98163   |  | MADE IN<br>USA<br>159-0435 L   |