

NSV Energy LLC
35 Hickory Springs Industrial Drive
Canton GA 30115



Stock # T110

Unused Hammond Power three phase transformer 112.5 kva, 3 phase, 60 hz, 150 Deg C rise 5.7 % Imp, Part No. NMK112BK , 220 deg C insulation system type K, Serial No. CB00730181, UL listed , Made in Mexico

Primary voltage: 480 Y/277 V

Secondary voltage 208 delta taps 218-213-208-203-198

Shipping size 31" x 28" x 46" H ' H 784 lbs



HP5 Hammond Power Solutions Inc.
GUELPH, ONT. BARABOO, WI COMPTON, CA MONTERREY, MX

LISTED
UL
DRY TYPE TRANSFORMER
17105
E112913

THREE PHASE DRY TYPE TRANSFORMER
TRANSFORMATEUR SEC TRIPHASE

LV/HT **480Y/277V**

BIL -

TERM. BORNES **H0 H1 H2 H3**

VOLTS	CURRENT COURANT	% RATED VOLTAGE % TENSION NOMINALE	CONNECTION EACH PHASE CONNEXION PAR PHASE
218	287.0	105	1
213	305.0	102.5	2
208	312.0	100	3
203	320.0	97.5	4
198	329.0	95	5

LV/HT **208V**

BIL -

TERM. BORNES **X1 X2 X3**

Diagram showing terminal connections: H2, H0, H3, X1, X2, X3, H1.

DO NOT INSTALL IN AREAS ACCESSIBLE TO PUBLIC
NE PAS INSTALLER DANS DES ENDROITS ACCESSIBLES AU PUBLIC

8 03423 54920 1

ADOM

Energy Efficiency
Efficacité d'énergie **CB02 2-00** TP 1-2002

SPACING BETWEEN ENCLOSURE AND KEY MOUNT
WALL SHALL BE A MINIMUM OF 8 INCHES
TRANSFORMER SUITABLE FOR STOP-UP OPERATION ONLY

Serial No. **CB00730181**
No. de série

Part No. **NMK112BK**
No. de pièce

kVA **112.5**

TYPE **K**

Cooling **ANN**
Refroidissement

Temp. Rise **150 C**
Echauffement

Temp. Class **220 C**
Classe de Temp.

Frequency **60 Hz**
Fréquence

Impedance % **5.7**
170 C

Encl. Type **3R**
Type de boîtier

Wt. LBS **745**
Poids en lbs.

Winding **AL**
Enroulement

CSA **NEMA**