

NSV Energy LLC
35 Hickory Springs Industrial Drive
Canton GA 30115



Stock # T121

Two (2) Unused GE dry type Transformer 225 kva, 3 phase, 60 hz , Catalog No 9T10A1007, Type QL, impedance 5.2/4.9 % , winding rise 150 deg C insul. Class 220 deg C, Type 2 enclosure , serial no.

1M00054ER/1M00054H4, UL listed, Made in Mexico

Primary voltage: 480 Delta 10 kv BIL Taps 506-493-480-468-455-442-430

Secondary voltage 208 Y/120, 10 kv BIL

Shipping Dimension: 48" L x 36"W x 56" H 1558 LB



Transformer
by ABB

Catalog Number **9T10A1007** Type **QL**

225.0 KVA 60 HZ 3 PH 4.9 % IMP
40 C AMB. 150 C RISE 220 C SYSTEM IS-19C

PRIMARY (H) 480 VOLTS (LINE-LINE)
SECONDARY (X) 208 VOLTS (LINE-LINE)
120 VOLTS (LINE-NEUTRAL)

JUMPER CONNECTION TAP VOLTS

1-2	503
2-3	492
3-4	480
4-5	469
5-6	457
6-7	446
7-8	435

COIL TAP ARRANGEMENT

ENCLOSURE TYPE 2 (IP20), OR RAINPROOF TYPE 3R (IP22) WHEN PROVIDED SHIELD 9T18Y1077G06

BEFORE HANDLING, INSTALLING AND OPERATING, SEE INSTRUCTION 475A667AAP009
ALUMINUM CONDUCTOR PRIMARY: 10 KV BIL SECONDARY: 10 KV BIL
IN ACCORDANCE WITH NEC SECTION 450-9, ALLOW AT LEAST SIX INCHES CLEARANCE FOR VENTILATION.
CHECK ADDITIONAL NEC AND LOCAL CODE

NEMA CLASS AA DRY TYPE TRANSFORMER Meets DOE 2016 efficiency

ASSEMBLED IN MEXICO

Note: Outline: 303B112GEDY17A

NET WGT 1188 LB INSPECTION & FINAL TEST 538.9 Kg NP3 90733 N226@ DY17A 062422

UL Energy Verified EV519886 LISTED 769G

1M00054H4