

NSV Energy LLC
35 Hickory Springs Industrial Drive
Canton GA 30115



Stock # T126

Hammond Transformer 150 kva, 3 phase, 60 hz , Cooling ANN

Primary voltage: 480 Delta Taps 504-492-480-468-456-444-432

Secondary voltage 240 v delta

Catalog No NMK150KD , Type K Winding AL impedance 6% winding rise 150 deg C

Enclosure NEMA-3R , Made in Mexico

Shipping Dimension: 40" L x 36" W x 49" H 957 lbs



HP5 Hammond Power Solutions Inc.
GUELPH, ONT. BARABOO, WI COMPTON, CA MONTERREY, MX

THREE PHASE DRY TYPE TRANSFORMER
TRANSFORMATEUR SEC TRIPHASE

HV/HT **480V**

BIL **-**

TERM. BORSES **H1 H2 H3**

VOLTS	CURRENT COURANT	% RATED VOLTAGE % TENSION NOMINALE	CONNECTION EACH PHASE CONNEXION PAR PHASE
504	172.0	105	1
492	176.0	102.5	2
480	180.0	100	3
468	185.0	97.5	4
456	190.0	95	5
444	195.0	92.5	6
432	200.0	90	7

LV/BT **240V**

BIL **-**

TERM. BORSES **X1 X2 X3**

TYPE K

Cooling **ANN**

Temp. Rise **150 C**

Temp. Class **220 C**

Freque. **60 Hz**

Impedance **6**

Encl. Type **NEMA-3R**

Wt LBS **940**

Winding **AL**

Enroulement **NEMA**

Energy Efficiency **CS02.2-00**

TP 1-2002

SPACING BETWEEN ENCLOSURE AND ADJACENT
WALL, SHALL BE A MINIMUM OF 8 INCHES
XX = 120V CT, 90% OF KVA RATING MAXIMUM

VERIFIED
CSA
VERIFIE

05423 04941 6